

DC4, Advanced Desktop Charger for d62 and d41

Features

- Charging status indicated in telephone display
- Supports remote management of portables
- Supports programming of portables
- Tilted design for stable operation of telephone and easy viewing of telephone display
- Telephone can be used with full functionality while in charger
- Easy to wipe clean
- USB connection
- Ethernet connection
- Supports easy replacement of telephones
- Ethernet switch functionality



Technical Specifications

Physical

| | |
|-------------------------|-----------------------------|
| Dimensions (l × w × h): | 130 × 98 × 55 mm |
| Weight: | 160 g (excl. power adapter) |
| Material: | Case: PC/ABS Rubber feet |
| Colour: | Steel grey |

Functional

| | |
|-----------------|--|
| Supply voltage: | 100 - 240 V, 50 - 60 Hz AC (adapter), 5 V DC (charger) |
| Charge current: | 0.65 A |

Interfaces

| | |
|-----------|--|
| USB: | USB specification 2.0 full speed |
| Ethernet: | Support data transfer rates up to 100Mbps (IEEE802.3 standard) |

Environmental

| | |
|-------------------------------------|---|
| Operating temperature: | +5°C to +40°C |
| Storage temperature: | -20°C to +65°C |
| Enclosure protection: | IP30, IEC EN60529 |
| Immunity to electromagnetic fields: | 3 V/m EN61000-4-3 |
| Immunity to ESD: | 4 kV contact discharge and 8 kV air discharge (EN61000-4-2) |

Compliance to European regulations and standards

| | |
|------------------|---------------------------------|
| EU directives: | 2004/108/EC(EMC) |
| Product marking: | CE |
| Safety: | EN60950-1 |
| EMC: | EN 55022 (class B), EN61000-4-3 |


Compliance to US regulations and standards

| | |
|------------------|---|
| Product marking: |  |
| Safety: | UL 60950-1 |
| EMC: | FCC CFR 47 Part 15 |

Compliance to Canadian regulations and standards

| | |
|------------------|--|
| Product marking: |  |
| Safety: | CSA 60950-1 |
| EMC: | FCC CFR 47 Part 15 |

Compliance to Australian regulations and standards

| | |
|------------------|---|
| Product marking: |  |
| Safety: | IEC 60950-1 |
| EMC: | EN 55022 (class B), EN61000-4-3 |

Specifications are subject to change without notice.