

Features	Results
Vendor	AudioCodes
Type	Mediant 1000
Firmware Version	5.60A.018.005
Tested with Swyxware Version	6.20 QF5
Date of Test	31.08.2009
Tester	Patrick Koetter
SIP Registration CPE (with / without authentication)	OK / OK
Correct registration behavior (re-reg. time out / keep alive)	OK / options or registration
Common call delivery (incoming call / outgoing call)	OK / OK
Simultaneous calls / group calls	OK / OK
Multiple accounts (1 IP-Adress - N Registrations)	not OK
CLIP support (incoming call / outgoing call / DDI)	OK / OK
Calling party number position inbound (RFC 3325 / from header / ...)	P-Asserted Identity
Calling party number position outbound (RFC 3325 / from header / ...)	P-Asserted Identity
NumberFormat outbound calling party	Subscriber
NumberFormat outbound called party	Subscriber
NumberFormat inbound calling party	Subscriber
NumberFormat inbound called party	Subscriber
CLIR	OK
CLIR method (anonymous / RFC 3325)	RFC3325
CLIP no screening	OK
Call hold (set on hold / release hold / hold music)	OK / OK / OK
Hold method (RFC 2543 (0.0.0.0) / RFC 3261 (sendonly)	sendonly
Call waiting / call swap	OK / OK
Call transfer (SIP refer)	OK
Conference call	OK
Call redirection / call rejection / call forwarding / follow me	OK / OK / OK
long duration call at least 30min (incoming / outgoing)	OK / OK
DTMF (SIP INFO relay / RFC 2833)	Info (Cisco) / RFC 2833 (not verified)
Codec support (a-law / μ -law / G729 / G722)	OK (not verified) / OK / OK / NS
Fax T.38 (incoming Fax / outgoing Fax)	OK
T.38 method	Streamswitch on CNG tone
Support of NAT traversal (STUN / SBC)	(OK / not supported)
Standby- (Fallback) Support / alternative registrar & proxy	OK / OK
Comment:	Swyxware 6.20 QF5 is needed (P-Asserted Identity)

